

- Designed for domestic use in smaller fittings.



Energy
efficient

FEATURES

- High lumen output efficiency
- Long lifetime 15000hrs
- Edison screw and bayonet cap available
- Low surface temperature for extra safety

APPLICATIONS

- Residential
- Retail
- Cafes
- Restaurants
- Display areas
- Atriums and heritage applications

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
	Non dim		E14 B15 E27 B22

Part No.	Model No.	Voltage	Watt.	PF	CCT.	Cap	Ra	Lumen	Beam Angle	Lifetime L70B50
132303	YKG45C7-5.9W	220-240V	5.9W	0.5	3000K	E27	≥80	470lm	225°	15000h
132304	YKG45C7-5.9W	220-240V	5.9W	0.5	3000K	B22	≥80	470lm	225°	15000h
132301	YKG45C7-5.9W	220-240V	5.9W	0.5	3000K	E14	≥80	470lm	225°	15000h
132302	YKG45C7-5.9W	220-240V	5.9W	0.5	3000K	B15	≥80	470lm	225°	15000h
132603	YKG45C7-5.9W	220-240V	5.9W	0.5	6500K	E27	≥80	500lm	225°	15000h
132604	YKG45C7-5.9W	220-240V	5.9W	0.5	6500K	B22	≥80	500lm	225°	15000h
132601	YKG45C7-5.9W	220-240V	5.9W	0.5	6500K	E14	≥80	500lm	225°	15000h
132602	YKG45C7-5.9W	220-240V	5.9W	0.5	6500K	B15	≥80	500lm	225°	15000h

[1]Operating Frequency=50/60Hz

[2]Switch Times≥20000