

- This versatile floodlight can be mounted horizontally to offer ease of installation and great utility.



**Slimline depth -
only 39mm**

FEATURES

- Pressed sheet metal body
- Built-in high efficiency SMD chips
- Constant current LED driver fitted
- Tempered glass
- IP65 weatherproof and IK07 vandal-proof
- High performance aluminium reflector
- Angle of support is adjustable up to 90°
- Fitting colour: Black

INCLUDES

- LED floodlight with driver
- 1.5 m flex and 3 pin plug

INSTALLATION OPTIONS

- Surface mounted

APPLICATIONS

- Parks
- Car parks
- Gardens
- Commercial
- Light industrial

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)	IK RATING

Part No.	Voltage	Watt.	PF	CCT.	Ra	Lumen	Beam Angle	Lifetime L70B50	Size(L*W*H)mm
272001	220-240V	10W	0.9	4000K	≥80	850lm	100°	35000h	149*105*39
272002	220-240V	20W	0.9	4000K	≥80	1700lm	100°	35000h	185*135*39
272003	220-240V	30W	0.9	4000K	≥80	2700lm	100°	35000h	300*203*39
272004	220-240V	50W	0.9	4000K	≥80	4500lm	100°	35000h	300*203*39
272501	220-240V	10W	0.9	5000K	≥80	850lm	100°	35000h	149*105*39
272502	220-240V	20W	0.9	5000K	≥80	1700lm	100°	35000h	185*135*39
272503	220-240V	30W	0.9	5000K	≥80	2700lm	100°	35000h	300*203*39
272504	220-240V	50W	0.9	5000K	≥80	4500lm	100°	35000h	300*203*39

Part No.	Model No.	VEET Status	IPART Status
272001 272501	YKFLA2-10W	Approved VEET No.: 4715	Approved IPART No.: 24143S14-ZDIID
272002 272502	YKFLA2-20W	Approved VEET No.: 4715	Approved IPART No.: 24143S14-ZDIID
272003 272503	YKFLA2-30W	Approved VEET No.: 4715	Approved IPART No.: 24143S14-ZDIID
272004 272504	YKFLA2-50W	Approved VEET No.: 4715	Approved IPART No.: 24143S14-ZDIID

[1]Operating Frequency=50/60Hz

[2]Switch Times≥20000

Specifications are for reference only and may be changed without prior notification.

Version: C_V3.1-02