



- Introduced to meet the needs of project builders seeking an ultra low cost yet performance downlight.


New!

FEATURES

- Plastic downlight with internal aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- Opal polycarbonate diffuser
- IC-4 rating. May be installed under ceiling insulation
- Removable flex and plug
- 6mm terminals for hard wiring

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Fixed head LED downlight
- Build-in dimmable LED driver
- 1.2 m flex and plug

APPLICATIONS

- Residential
- Hotels and shops
- Conference rooms
- Reception areas
- Bathrooms and wet areas

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION		IP RATING	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
			 leading and trailing edge		

Part No.	Voltage	Watt.	PF	CCT.	Ra	Lumen	Beam Angle	Lifetime L70B50	Fitting Colour
173083	220-240V	9W	0.9	3000K	≥80	750lm	100°	35000h	White
173084	220-240V	9W	0.9	4000K	≥80	800lm	100°	35000h	White
173085	220-240V	9W	0.9	5000K	≥80	800lm	100°	35000h	White

Part No.	Model No.	VEET Status	IPART Status
173083	YKRS3F5B-D 9W	Approved VEET No.: 5425	Approved IPART No.: 24143D15-LQPIHHF
173084	YKRS3F5B-D 9W	Approved VEET No.: 5425	Approved IPART No.: 24143D15-LQPIHHF
173085	YKRS3F5B-D 9W	Approved VEET No.: 5425	Approved IPART No.: 24143D15-LQPIHHF

[1] Operating Frequency=50/60Hz

[2] Switch Times≥20000

[3] This fitting is IP54 only once installed