

- A durable classic performer with chrome trim.



Removable
satin chrome
ring

FEATURES

- Surface mounted oyster light
- High efficiency SMD chips
- Powder coated steel base
- Opal PMMA diffuser
- Satin chrome rim

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Constant current dimmable LED driver
- Mounting accessories

APPLICATIONS

- Residential
- Hallways
- Stairwells
- Porches
- Walls ceilings

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	DISTRIBUTION		DIMENSIONS(mm)
		leading and trailing edge			

Part No.	Voltage	Watt.	PF	CCT.	Ra	Lumen	Beam Angle	Lifetime L70B50	Fitting Colour
182013	220-240V	14W	0.9	3000K	≥80	1000lm	120°	20000h	Satin Chrome
182014	220-240V	14W	0.9	4000K	≥80	1100lm	120°	20000h	Satin Chrome
182015	220-240V	26W	0.9	3000K	≥80	1800lm	120°	20000h	Satin Chrome
182016	220-240V	26W	0.9	4000K	≥80	1900lm	120°	20000h	Satin Chrome

Part No.	Model No.	VEET Status	IPART Status
182013	YKCLE1R3-D-14W	Approved VEET No.: 4713	Approved IPART No.: 24143S13-PGEHIAS
182014	YKCLE1R3-D-14W	Approved VEET No.: 4713	Approved IPART No.: 24143S13-PGEHIAS
182015	YKCLE1R3-D-26W	Approved VEET No.: 4713	Approved IPART No.: 24143S13-PGEHIAS
182016	YKCLE1R3-D-26W	Approved VEET No.: 4713	Approved IPART No.: 24143S13-PGEHIAS

[1] Operating Frequency=50/60Hz

[2] Switch Times≥20000

[3] For dimming compatibility please see page 88