Fixed Downlights

VIVA Multi 110

VIVA110-MULTI

SAP CODE: 2000509



110mm, 9W, switchable colour temperature, flush diffuser, LED fixed downlight

A white trimmed LED downlight with flush opal diffuser that has a range of clip on trims - gold, brushed nickel and black. It can be dimmed and switched to three colour temperatures.

Accessories

ADAPTOR RING; CLIP-ON TRIM ROUND

Photometric Diagram



Unit: cd
– C0/180 80.0deg
– C90/270 80.0deg

KEY INFORMATION

Lumen Output	840 / 880 / 850lm
Input Power	9W
Hole Cutout Size	Ø90-110mm
Install	RECESSED
Dimming Options	*Phase-Cut Dimming
Trim Colour	WHITE
Warranty	4yr
IP Rating	IP44
IK Rating	N/A
IC Rating	IC-4
Rebate Scheme Approvals	VEET; REES; IPART LCP 8.72

PHOTOMETRIC

Efficacy	94 / 98 / 94lm/W
LED	SMD
CCT	3000 / 4200 / 5700K
CRI	>80
Beam Angle	90°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	72VDC
Power Factor	>0.9
LED Input Current (nominal)	125mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium + Polycarbonate
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Rubberised Clip
Connection Type	1.1m Flex & Plug
Total Weight	0.22kg
Dimensions	Ø110x65mm
Operating Ambient Temp.	-25 to 50°C
Electrical Classification	Class 2

*Dimming performance may vary depending on the specifications of the dimmer being used. For best performance use the Haneco DUO-350W dimmer.

Specification subject to change without prior notice. Last updated 3/09/2018