

- A range of the most popular A60 lamps for domestic and office use.



Same size
and similar light
output of
conventional
A60 lamps

FEATURES

- High lumen output efficiency
- Edison screw and bayonet cap available
- Low temperature for safety
- Delivering nearly the same light output as an incandescent bulb
- Long lifetime 15000hrs

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

APPLICATIONS

- Residential
- Retail
- Cafes
- Restaurants
- Display areas
- Atriums and heritage applications

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
	 leading and trailing edge		

Part No.	Model No.	Voltage	Watt.	PF	CCT.	Cap	Ra	Lumen	Beam Angle	Lifetime L70B50
112091C	YKA60C7-D-5.5W	220-240V	5.5W	0.7	3000K	E27	≥80	470lm	240°	15000h
112092C	YKA60C7-D-5.5W	220-240V	5.5W	0.7	3000K	B22	≥80	470lm	240°	15000h
112093C	YKA60C7-D-5.5W	220-240V	5.5W	0.7	4000K	E27	≥80	490lm	240°	15000h
112094C	YKA60C7-D-5.5W	220-240V	5.5W	0.7	4000K	B22	≥80	490lm	240°	15000h
112095C	YKA60C7-D-5.5W	220-240V	5.5W	0.7	6500K	E27	≥80	490lm	240°	15000h
112096C	YKA60C7-D-5.5W	220-240V	5.5W	0.7	6500K	B22	≥80	490lm	240°	15000h
112103C	YKA60C7-D-8.7W	220-240V	8.7W	0.7	3000K	E27	≥80	806lm	240°	15000h
112104C	YKA60C7-D-8.7W	220-240V	8.7W	0.7	3000K	B22	≥80	806lm	240°	15000h
112105C	YKA60C7-D-8.7W	220-240V	8.7W	0.7	4000K	E27	≥80	840lm	240°	15000h
112106C	YKA60C7-D-8.7W	220-240V	8.7W	0.7	4000K	B22	≥80	840lm	240°	15000h
112107C	YKA60C7-D-8.7W	220-240V	8.7W	0.7	6500K	E27	≥80	840lm	240°	15000h
112108C	YKA60C7-D-8.7W	220-240V	8.7W	0.7	6500K	B22	≥80	840lm	240°	15000h
112073C	YKA60C7-D-9.2W	220-240V	9.2W	0.7	3000K	E27	≥80	1055lm	240°	15000h
112074C	YKA60C7-D-9.2W	220-240V	9.2W	0.7	3000K	B22	≥80	1055lm	240°	15000h
112077C	YKA60C7-D-9.2W	220-240V	9.2W	0.7	4000K	E27	≥80	1148lm	240°	15000h
112078C	YKA60C7-D-9.2W	220-240V	9.2W	0.7	4000K	B22	≥80	1148lm	240°	15000h
112081C	YKA60C7-D-9.2W	220-240V	9.2W	0.7	6500K	E27	≥80	1148lm	240°	15000h
112082C	YKA60C7-D-9.2W	220-240V	9.2W	0.7	6500K	B22	≥80	1148lm	240°	15000h

[1]Operating Frequency=50/60Hz; [2]Switch Times≥20000; [3] For dimming compatibility please see page 91

Specifications are for reference only and may be changed without prior notification.

Version: C_V3.1-01