

- Introduced to replace many inefficient candle lamps in candelabras and similar fittings.



Low energy

FEATURES

- High lumen output efficiency
- Long lifetime 15000hrs
- Edison screw and bayonet cap available
- Low surface temperature for extra safety

APPLICATIONS

- Residential
- Retail
- Cafes
- Restaurants
- Display areas
- Atriums and heritage applications

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
	Non dim		E14 E27 B15 B22

Part No.	Model No.	Voltage	Watt.	PF	CCT.	Cap	Ra	Lumen	Beam Angle	Lifetime L70B50
122303	YKC35C7-5.9W	220-240V	5.9W	0.5	3000K	E27	≥80	470lm	300°	15000h
122304	YKC35C7-5.9W	220-240V	5.9W	0.5	3000K	B22	≥80	470lm	300°	15000h
122301	YKC35C7-5.9W	220-240V	5.9W	0.5	3000K	E14	≥80	470lm	300°	15000h
122302	YKC35C7-5.9W	220-240V	5.9W	0.5	3000K	B15	≥80	470lm	300°	15000h
122603	YKC35C7-5.9W	220-240V	5.9W	0.5	6500K	E27	≥80	500lm	300°	15000h
122604	YKC35C7-5.9W	220-240V	5.9W	0.5	6500K	B22	≥80	500lm	300°	15000h
122601	YKC35C7-5.9W	220-240V	5.9W	0.5	6500K	E14	≥80	500lm	300°	15000h
122602	YKC35C7-5.9W	220-240V	5.9W	0.5	6500K	B15	≥80	500lm	300°	15000h

[1]Operating Frequency=50/60Hz

[2]Switch Times≥20000