

- A robust oyster for domestic and office applications.



Clean
and
efficient

FEATURES

- Surface mounted oyster light
- High efficiency SMD chips
- Powder coated steel base
- Opal PMMA diffuser
- IP54 weatherproof

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Constant current dimmable LED driver
- Mounting accessories

APPLICATIONS

- Residential
- Hallways
- Stairwells
- Porches
- Walls ceilings
- Bathrooms and wet areas

WARRANTY

- Five years (subject to terms and conditions)

| CERTIFICATION | IP RATING | DIMMABLE | DISTRIBUTION | | DIMENSIONS(mm) | |
|---------------|-----------|---------------------------|--------------|--|----------------|--|
| | | leading and trailing edge | | | | |

| Part No. | Voltage | Watt. | PF | CCT. | Ra | Lumen | Beam Angle | Lifetime L70B50 | Fitting Colour |
|----------|----------|-------|-----|-------|-----|--------|------------|-----------------|----------------|
| 182017 | 220-240V | 14W | 0.9 | 3000K | ≥80 | 1000lm | 120° | 20000h | White |
| 182018 | 220-240V | 14W | 0.9 | 4000K | ≥80 | 1100lm | 120° | 20000h | White |
| 182021 | 220-240V | 26W | 0.9 | 3000K | ≥80 | 1800lm | 120° | 20000h | White |
| 182022 | 220-240V | 26W | 0.9 | 4000K | ≥80 | 1900lm | 120° | 20000h | White |

| Part No. | Model No. | VEET Status | IPART Status |
|----------|-------------------|-------------------------|---------------------------------------|
| 182017 | YKCLE1R3WHO-D-14W | Approved VEET No.: 4714 | Approved IPART No.: 24143S13-DIJFGGFH |
| 182018 | YKCLE1R3WHO-D-14W | Approved VEET No.: 4714 | Approved IPART No.: 24143S13-DIJFGGFH |
| 182021 | YKCLE1R3WHO-D-26W | Approved VEET No.: 4714 | Approved IPART No.: 24143S13-DIJFGGFH |
| 182022 | YKCLE1R3WHO-D-26W | Approved VEET No.: 4714 | Approved IPART No.: 24143S13-DIJFGGFH |

[1] Operating Frequency=50/60Hz

[2] Switch Times≥20000

[3] For dimming compatibility please see page 88