

- Dual wattage modular batten.



New!

*Bi-level power switch on driver



FEATURES

- Built-in high efficiency SMD chips
- Powder coated steel base
- Highly transparent opal polycarbonate diffuser
- Variable wattage, switch between 10/21W, 21/42W
- Large 6mm terminal block for easy installation
- Quick install modular design
- Fitting colour: White

INCLUDES

- LED Batten
- Dual wattage / light output switchable driver
- Mounting accessories

INSTALLATION OPTIONS

- Surface mounted
- Suspended(suspension kit is required)

APPLICATIONS

- Offices
- Garages
- Stations
- Industrial

WARRANTY

- Five years (subject to terms and conditions)

| CERTIFICATION | IP RATING | DIMMABLE | DISTRIBUTION | | DIMENSIONS(mm) |
|---------------|-----------|----------|--------------|--|----------------|
| | | | | | |

| Part No. | Voltage | Watt. | PF | CCT. | Ra | Lumen | Beam Angle | Lifetime L70B50 | Size(L*W*H)mm |
|----------|----------|---------|-----|-------|-----|-------------|------------|-----------------|---------------|
| 213064 | 220-240V | 10W/21W | 0.9 | 4000K | ≥80 | 1000/2100lm | 120° | 50000h | 600*69*72 |
| 213074 | 220-240V | 21W/42W | 0.9 | 4000K | ≥80 | 2100/4200lm | 120° | 50000h | 1200*69*72 |
| 213066 | 220-240V | 10W/21W | 0.9 | 6500K | ≥80 | 1000/2100lm | 120° | 50000h | 600*69*72 |
| 213076 | 220-240V | 21W/42W | 0.9 | 6500K | ≥80 | 2100/4200lm | 120° | 50000h | 1200*69*72 |

| Part No. | Model No. | VEET Status | IPART Status |
|----------|-----------------|-------------|--------------|
| 213064 | BTA1F-2L60 21W | Pending | Pending |
| 213074 | BTA1F-2L120 42W | Pending | Pending |
| 213066 | BTA1F-2L60 21W | Pending | Pending |
| 213076 | BTA1F-2L120 42W | Pending | Pending |

[1] Operating Frequency=50/60Hz

[2] Switch Times≥25000