

- Multi-purpose budget interior luminaire.



Ideal for domestic applications.
Available in both white and chrome trims

FEATURES

- Surface mounted oyster light
- High efficiency SMD chips
- PBT Base
- Opal polycarbonate diffuser
- Available colour rings: white PBT or steel satin chrome

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Internal dimmable constant current driver
- Mounting accessories

APPLICATIONS

- Residential
- Hallways
- Stairwells
- Porches
- Walls ceilings

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
		leading and trailing edge		

Part No.	Voltage	Watt.	PF	CCT.	Ra	Lumen	Beam Angle	Lifetime L70B50	Fitting Colour
182003	220-240V	13W	0.9	3000K	≥80	820lm	120°	25000h	White
182007	220-240V	13W	0.9	4000K	≥80	900lm	120°	25000h	White
182004	220-240V	13W	0.9	3000K	≥80	820lm	120°	25000h	Satin Chrome
182008	220-240V	13W	0.9	4000K	≥80	900lm	120°	25000h	Satin Chrome

Part No.	Model No.	VEET Status	IPART Status
182003	YKCLE0W32-D-13W	Approved VEET No.: 4349	Approved IPART No.: 24143S13-SEGEIFEJ
182007	YKCLE0W32-D-13W	Approved VEET No.: 4349	Approved IPART No.: 24143S13-SEGEIFEJ
182004	YKCLE0B32-D-13W	Approved VEET No.: 4453	Approved IPART No.: 24143D13-EF5MJF
182008	YKCLE0B32-D-13W	Approved VEET No.: 4453	Approved IPART No.: 24143D13-EF5MJF

[1] Operating Frequency=50/60Hz

[2] Switch Times≥20000

[3] For dimming compatibility please see page 87