




18W - 22W COB DOWNLIGHT


COB downlights consume less power compared with conventional commercial lighting products. At the same time offering high light output, 40,000 + hours life, with excellent light stability and colour render.

Product Code	Voltage (V)	Wattage (W)	Power Factor	Luminous Flux (Lm)	Beam Angle	Cutout size (mm)	Colour temp	Dimmable
DL41120CW	240V AC	18W	>0.85	1250	60	95	6000 (CW)	Yes
DL41120NW	240V AC	18W	>0.85	1210	60	95	5000 (NW)	Yes
DL41120WW	240V AC	18W	>0.85	1170	60	95	3200 (WW)	Yes
DL42140CW	240V AC	22W	>0.85	1575	60	125	6000 (CW)	Yes
DL42140NW	240V AC	22W	>0.85	1515	60	125	5000 (NW)	Yes
DL42140WW	240V AC	22W	>0.85	1485	60	125	3200 (WW)	Yes

Note : Lights are available in silver or white finish



	BEAM ANGLE 60 DEG		
	Distance (M)	Avg/Max (lux)	Diameter (M)
	1	1043	1.08
	1.5	464	1.61
	2	261	2.15
	2.5	166	2.69
	3	116	3.23

	BEAM ANGLE 60 DEG		
	Distance (M)	Avg/Max (lux)	Diameter (M)
	1	1320	1.08
	1.5	586	1.61
	2	330	2.15
	2.5	211	2.69
	3	146	3.23