

- Robust circular bulkhead .



Die-cast metal
base with
polycarbonate
diffuser

FEATURES

- Die-cast aluminium body
- Built-in high efficiency SMD chips
- Constant current driver fitted
- Opal polycarbonate diffuser
- IP65 weatherproof and IK10 vandal-proof
- Large 6mm terminal block for easy installation
- Fitting colour: Black

INCLUDES

- LED bunker with driver
- Mounting accessories

INSTALLATION OPTIONS

- Surface mounted

APPLICATIONS

- Walkways
- Hallways
- Balconies
- Industrial
- Commercial

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	DISTRIBUTION		DIMENSIONS(mm)		IK RATING

Part No.	Voltage	Watt.	PF	CCT.	Ra	Lumen	Beam Angle	Lifetime L70B50	Fitting Colour
282010	100-240V	9W	0.9	3000K	≥80	600lm	110°	50000h	Black
282011	100-240V	9W	0.9	4000K	≥80	650lm	110°	50000h	Black
282012	100-240V	9W	0.9	5000K	≥80	650lm	110°	50000h	Black
282013	100-240V	18W	0.9	3000K	≥80	1350lm	110°	50000h	Black
282014	100-240V	18W	0.9	4000K	≥80	1450lm	110°	50000h	Black
282015	100-240V	18W	0.9	5000K	≥80	1450lm	110°	50000h	Black

Part No.	Model No.	VEET Status	IPART Status
282010 282011 282012	YKBHEB3-9W	Approved VEET No.: 4781	Approved IPART No.:24143S13-KJJJGYFD
282013 282014 282015	YKBHEB3-18W	Approved VEET No.: 4781	Approved IPART No.:24143S13-KJJJGYFD

[1]Operating Frequency=50/60Hz

[2]Switch Times≥25000